

Shenzhen JZD Wires & Cables Co.,Ltd

ADD:Building C, Liansheng Industrial Park, No.77 Yanshan Avenue, Baoan District, Shenzhen City

TEL : 0086 13510784550

E-mail : Manager@jzdcable.com

450/750V and below PVC insulated and nylon sheathed cable

Part Number	AWG Size	Conductor No./mm	Nom. O.D . (cm)	Nom. Insul. Thick. (cm)	Approx LBS/MFT	Ampacity @ 90°C
THHN 14 1	14	Solid	0.26	0.04	15	15
THHN 14 19	14	19/0.38	0.28	0.04	16	15
THHN 12 1	12	Solid	0.30	0.04	23	20
THHN 12 19	12	19/0.47	0.33	0.04	24	20
THHN 10 1	10	Solid	0.41	0.05	38	30
THHN 10 19	10	19/0.60	0.41	0.05	38	30
THHN 8 19	8	19/0.75	0.54	0.08	63	55
THHN 6 19	6	19/0.95	0.63	0.08	95	75
THHN 4 19	4	19/1.19	0.81	0.10	152	95
THHN 3 19	3	19/1.33	0.88	0.10	189	110
THHN 2 19	2	19/1.50	0.96	0.10	234	130
THHN 1 19	1	19/.0664	1.10	0.13	299	150
THHN 1/0 19	1/0	19/1.68	1.20	0.13	372	170
THHN 2/0 19	2/0	19/1.89	1.32	0.13	462	195
THHN 4/0 19	4/0	19/2.67	1.58	0.13	718	260