

Shenzhen JZD Wires & Cables Co.,Ltd

ADD:Building C, Liansheng Industrial Park, No.77 Yanshan Avenue, Baoan District, Shenzhen City

TEL : 0086 13510784550

E-mail : Manager@jzdcable.com

Certification

The Certification Certificate Of Quality Management System

Shenzhen Bao'an Jianzhenda Electric Wire Factory
 Address: 11/F, Building C, Liansheng Industrial Park, Yanshan Avenue, Baoan District, Shenzhen City, Guangdong, P.R. China. P.C. 518108
 Certificate No.: 18412010274005

According to your organization's application, our centre carried out audit and verification in accordance with the requirements for Quality Management System (ISO 9001:2015) and ISO 9001:2015, it accords with the requirements through assessment.

The scope of the certified QMS is:

Production and sales of PVC insulated flexible cable & wire, PVC insulated non-shield cable & wire, PVC insulated shield cable and electronic connecting line (excluding products required license)

Issue date: 2019-1-17
 Term of validity of this certificate: 2019-1-17 to 2021-1-17

The certified organization shall be subject to annual supervision of EC during the validity period. This Certificate is only valid with the named certificate holder.

Guangdong Quality Testing CTC Certification Co., Ltd.
 Address: 17/F, Huan Building, Yantian, Longgang District, Shenzhen, Guangdong, P.R.C.
 Tel: 400-888-8887 Fax: 836-888878
 Website: www.gdctc.com.cn P.C. 518108

Certificate of Compliance

No. 1118008JWJG34

Certificate's Holder: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 No. 77, Yanshan Road, Yantian Community, Songgang Street, Baoan District, Shenzhen, China

Certification ECM Mark:

Product: Wire and Cable
 Model(s): BVV 2.5mm², HDV-U, HDV-B, HDV-VHG-F, HDV-VVF, HDV-VHG-F, HDV-VF-F, HDV-VU, HDV-K, HDV-K

Verification to: Standard: EN 50323-2-31:2011, IEC 60227-3:1993+A1:1997
 related to CE Directive(s): 2014/53/EU (Low Voltage)

Notes: The product(s) has been verified on a voluntary basis. The product(s) attests the requirements of the Certification mark of ECM, supervised by the above listed body. The above Compliance mark can be affixed on the product(s) according to the CE mark regulation about its usage and its use. The obligation can be found at www.ecmcert.com. The Certificate of Compliance can be checked on website: www.ecmcert.com

ECM Mark:

Issue date: 04 May 2018
 Valid until: 07 Jun 2020

Guangdong Quality Testing CTC Certification Co., Ltd.
 No. 17/F, Huan Building, Yantian, Longgang District, Shenzhen, Guangdong, P.R.C.
 Tel: 400-888-8887 Fax: 836-888878
 Website: www.gdctc.com.cn P.C. 518108

IEC CB Certificate

Certificate No.: 2019010100780058

Applicant: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Address: No. 77 Yanshan Road, Yantian Community, Songgang Street, Baoan District, Shenzhen City, Guangdong, P.R. China

Manufacturer: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Address: No. 77 Yanshan Road, Yantian Community, Songgang Street, Baoan District, Shenzhen City, Guangdong, P.R. China

Factory: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Address: No. 77 Yanshan Road, Yantian Community, Songgang Street, Baoan District, Shenzhen City, Guangdong, P.R. China

Product Name, Model and Specification: PVC insulated non-sheathed wire and cables
 8027 IEC 018V 4070V 1.5-6, 8027 IEC 028V 3000V 1.5-6, 8027 IEC 0 30V 3000V 0.5-1, 8027 IEC 00V 3000V 0.5-1-RV 3000V 0.75-1, BV 40 015V 2.5-6, BV 40070V 2.5-6

Standards and Technical Requirements for the Products: GB/T3023.3-2008/IEC60227-3:1987, GB/T374.2-2016

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification/RETCO CNCA-0141:2014

Valid from: May 04, 2018 Valid until: May 04, 2020

The validity of the certificate is subject to positive result of the regular follow-up inspection by testing certification body until the expiry date.

Date of original issue: Jan 07, 2018

Further information is available through CNCA website: www.cnca.gov.cn

President:

China Quality Certification Centre
 No. 108, Zhongguo Road, Beijing 100013, P.R. China

ISO9001

CE

CB

RoHS Certificate of Compliance

Certificate's Holder: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Address: 11/F, Building C, Liansheng Industrial Park, Yanshan Avenue, Baoan District, Shenzhen City, Guangdong, P.R. China

Product Model(s): BVV 2.5mm², HDV-U, HDV-B, HDV-VHG-F, HDV-VVF, HDV-VHG-F, HDV-VF-F, HDV-VU, HDV-K, HDV-K

Standard: IEC 60227-3

Shanghai SHANG YANG

Shanghai SHANG YANG

SAA Certificate of Conformity *Addendum*

Certificate No.: SAA-200446-EA
 Date of Issue: 1 April 2020

Regulatory Definition: Building Wiring Cable
 Product Description: V 91 Standard, 74 92 Standard Flat Plastic Cable

Manufacturer	Trade Name	Rating	Manufacturer	Trade Name	Rating
Shenzhen Jianzhenda Wire & Cable Co., Ltd.	BVV 2.5mm ²	4070V	Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-U	4070V
Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-B	4070V	Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-VHG-F	4070V
Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-VVF	4070V	Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-VHG-F	4070V
Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-VF-F	4070V	Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-VU	4070V
Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-K	4070V	Shenzhen Jianzhenda Wire & Cable Co., Ltd.	HDV-K	4070V

Shanghai SHANG YANG

CCC Certificate for China Compulsory Product Certification

Certificate No.: 2019010100780058

Name and Address of the Applicant: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Block C Factory Building, No. 77 Yanshan Industrial Park, Yantian Road, Yantian Community, Songgang Sub-district, Baoan District, Shenzhen

Name and Address of the Manufacturer: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Block C Factory Building, No. 77 Yanshan Industrial Park, Yantian Road, Yantian Community, Songgang Sub-district, Baoan District, Shenzhen

Name and Address of the Factory: Shenzhen Jianzhenda Wire & Cable Co., Ltd.
 Block C Factory Building, No. 77 Yanshan Industrial Park, Yantian Road, Yantian Community, Songgang Sub-district, Baoan District, Shenzhen

Product Name, Model and Specification: PVC insulated non-sheathed wire and cables
 8027 IEC 018V 4070V 1.5-6, 8027 IEC 028V 3000V 1.5-6, 8027 IEC 0 30V 3000V 0.5-1, 8027 IEC 00V 3000V 0.5-1-RV 3000V 0.75-1, BV 40 015V 2.5-6, BV 40070V 2.5-6

The Standards and Technical Requirements for the Products: GB/T3023.3-2008/IEC60227-3:1987, GB/T374.2-2016

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification/RETCO CNCA-0141:2014

Valid from: May 04, 2018 Valid until: May 04, 2020

The validity of the certificate is subject to positive result of the regular follow-up inspection by testing certification body until the expiry date.

Date of original issue: Jan 07, 2018

Further information is available through CNCA website: www.cnca.gov.cn

President:

China Quality Certification Centre
 No. 108, Zhongguo Road, Beijing 100013, P.R. China

ROHS

SAA

CCC

Silicone Insulation Tinned Copper Silicone Cable

Conductor				Insulator		Electrical Characteristics	Maximum Current	Package
Size	No. & Nominal / Diameter of Wire	Section	Diameter	Insulator Thick	Over Diameter	Conductor resistance	Ampere	
AWG	MM	MM ²	MM	MM	MM	Ω/KM	A	Meter / Roll
0	19000/0.08mm	95.5	12.73	2.64	18	0.18	955	50
1	15000/0.008mm	75	11.3	2.3	15.5	0.45	840	50
2	10000/0.008mm	50	9.24	2.4	14	0.63	630	50
3	6700/0.008mm	33.7	7.73	2.6	13	0.89	500	50
4	5000/0.008mm	25	6.53	2.4	11	1.25	400	50
6	3200/0.008mm	16	5.23	1.65	8.5	1.9	300	100
7	2400/0.008mm	12	4.53	1.35	7.2	2.6	240	100
8	1650/0.008mm	8.3	3.75	1.5	6.3	3.7	190	100
10	1050/0.008mm	5.3	3	1.3	5.45	6.3	140	100
11	750/0.008mm	3.8	2.53	1.2	5	8.3	105	100
12	680/0.008mm	3.4	2.41	1	4.5	9.8	88	100
13	500/0.008mm	2.5	2.07	1	4	12.5	70	100
14	400/0.008mm	2	1.85	0.9	3.5	15.6	55	200
15	300/0.008mm	1.5	1.6	0.8	3.2	20.8	42	200
16	252/0.008mm	1.27	1.47	0.75	3	24.4	35	200
17	210/0.008mm	1	1.33	0.68	2.7	29.8	30	200
18	150/0.008mm	0.75	1.13	0.55	2.3	39.5	22	200
20	100/0.008mm	0.5	0.92	0.45	1.8	62.5	13	400
22	60/0.008mm	0.3	0.72	0.45	1.7	88.6	8	400
24	40/0.008mm	0.2	0.58	0.5	1.6	97.6	5	400
26	30/0.008mm	0.16	0.51	0.5	1.5	123	3.5	400
28	16/0.008mm	0.08	0.37	0.4	1.2	227.2	1.25	1500
30	11/0.008mm	0.055	0.31	0.3	0.8	331	0.8	2500